

JK-TU62 / -TU63H SPECIFICATION SHEET

Main features: 3CCD, 1/2" or 1/3" RGB micro prism system, remote head colour camera, VBS, Y/C,RGB, digital RGB (LVDS) 10bit/colour out, 2:1 interlaced 800/750 TV lines, S/N 64 dB, C mount



JK-TU62H	1/2" 3CCD remote head
Specifications	
Image sensor	1/2inch IT-CCD
Effective pixels	Horizontal: 752 pixels, Vertical: 582 pixels
Horizontal resolution	800TV lines
Sensitivity	F11 standard (2000lx, 3000K)
Minimum illumination	4 lx (F2.2, Sensitivity + 20dB, 3000K)
SN ratio	64dB standard
Lens mount	C Mount (flange back: 17.526mm in-air)
Ambient temperature	32 to 104° F (0°to 40°C)
Ambient humidity	Less than 90%
Weight	Approx. 2.82 oz (80g)
JK-TU63H	
1/3" 3CCD remote head	
Specifications	
Image sensor	1/3inch IT-CCD
Effective pixels	Horizontal: 752 pixels, Vertical: 582 pixels
Horizontal resolution	750TV lines
Sensitivity	F11 standard (2000lx, 3000K)
Minimum illumination	4 lx (F2.2, Sensitivity + 20dB, 3000K)
SN ratio	64dB standard
Lens mount	C-Mount (flange back: 17.526mm in-air)
Ambient temperature	32 to 104° F (0°to 40°C)
Ambient humidity	Less than 90%
Weight	Approx. 1.94 oz (55g)

Design and specifications are subject to change without notice

TOSHIBA EUROPE GmbH Internet: www.toshiba.ch/ics
 Chriesbaumstrasse 4 Email: andre.beer@toshiba.ch
 CH 8604 Volketswil Tel: +41 (0)1 908 56 34
 Switzerland Fax: +41 (0)1 908 56 57

Distributor